

Compact Track Loaders / T740 Compact Track Loader

T740 Loader Specifications & Options

■ Standard
 ✓ Optional
 N/A Not Applicable

Units US

Bobcat T740

Configuration

Standard

Roller Suspension Option

Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	<input checked="" type="checkbox"/>

Performance

Rated Operating Capacity (ISO)	3,310 lb
Operating Capacity (50% of Tip)	4571 lb
Tipping Load	9143 lb
Operating Weight	10127 lb
Travel Speed	6 mph
Travel Speed (2-speed option)	8.3 mph
Ground Pressure (Rubber)	4.1 psi

Capacities

Fuel Tank	43.8 gal
-----------	----------

Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23 gal/min
Auxiliary High Flow	30.5 gal/min

Dimension

Length	114.3 in
Length without Attachment	114.3 in
Length with Standard Bucket	141.6 in
Width	78 in
Width (with bucket)	80 in
Height	81.3 in
Height with Operator Cab	81.3 in
Height to Bucket Hinge Pin	131 in
Reach @ Maximum Height	35.2 in
Turning Radius	88 in
Length of track on ground	63.7 in
Track Width	17.7 in
Track Width - Optional	12.6 in

Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	N/A
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.